(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Date of compilation: 30/10/2019 **Version 1**

Page 1 of 12 Print date: 20/11/2024 **Version 26 (replaces version 25)** Revision date: 06/03/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Nail Free Fix Product Code: 110441

FN40-70K9-9006-JMFV UFI:

1.2 Relevant identified uses of the substance or mixture and uses advised against.

ADHESIVO MULTIUSOS

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

BSF - Bond | Seal | Fill Company:

Address: Camino de Sierra, 34

PO Box: 67

Province: Alicante (España) E-mail: info@bsfintl.com www.bsfintl.com Web:

1.4 Emergency telephone number: (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: Causes serious eye irritation.

Flam. Liq. 2: Highly flammable liquid and vapour. STOT SE 3: May cause drowsiness or dizziness.

Skin Irrit. 2: Causes skin irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:





Signal Word:

Danger

Hazard statements:

Highly flammable liquid and vapour. H225

H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects. H412

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Date of compilation: 30/10/2019 Version 1

Page 2 of 12 Version 26 (replaces version 25) Revision date: 06/03/2024 Print date: 20/11/2024

P273 Avoid release to the environment.

 $We ar protective \ gloves/protective \ clothing/eye \ protection/face \ protection/hearing \ protection/...$ P280

P370+P378 In case of fire: Use extinguisher powder or CO2 for extinction. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Contains:

ethyl acetate

hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6)) (Mixture of isomers)

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 607-022- 00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01- 2119475103-46-XXXX	[1] ethyl acetate	10 - 19.99 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Registration No: 01- 2119484651-34-XXXX	hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6)) (Mixture of isomers)	10 - 19.99 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT SE 3, H336 - Skin Irrit. 2, H315	-
Index No: 601-022- 00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01- 2119488216-32-XXXX	I-20-7 35-7 Io: 01-		Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 128-37-0 EC No: 204-881-4 Registration No: 01- 2119565113-46-XXXX	2,6-di-tert-butyl-p-cresol	0.25 - 2.49 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

^{*} See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

^[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

^[2] Substance with a national workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Version 1 Date of compilation: 30/10/2019

Version 26 (replaces version 25) Revision date: 06/03/2024



Print date: 20/11/2024

Page 3 of 12

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as

reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Carbon monoxide, carbon dioxide.
- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Date of compilation: 30/10/2019 Version 1

Page 4 of 12 **Version 26 (replaces version 25)** Revision date: 06/03/2024 Print date: 20/11/2024



SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

7.3 Specific end use(s).

Refer to technical data sheet available on request.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

(in accordance with Regulation (EU) 2020/878)



Date of compilation: 30/10/2019 Version 1

Page 5 of 12 Version 26 (replaces version 25) Revision date: 06/03/2024 Print date: 20/11/2024

Name	CAS No.	Country	Limit value	ppm	mg/m³
othyd acotato	141-78-6	European	Eight hours	200	734
ethyl acetate	141-78-0	Union [1]	Short term	400	1468
vadono	1330-20-7	European	Eight hours	50 (skin)	221 (skin)
xylene	1330-20-7	Union [1]	Short term	100 (skin)	442 (skin)

^[1] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL	Inhalation, Chronic, Systemic effects	734
	(Workers)		(mg/m³)
	DNEL	Inhalation, Chronic, Local effects	734
	(Workers)		(mg/m³)
	DNEL	Inhalation, Chronic, Local effects	367
ethyl acetate	(Consumers)		(mg/m³)
CAS No: 141-78-6	DNEL	Inhalation, Short term, Local effects	1468
EC No: 205-500-4	(Workers)		(mg/m³)
LC 140: 203 300 1	DNEL	Inhalation, Short term, Local effects	734
	(Consumers)		(mg/m³)
	DNEL	Dermal, Chronic, Systemic effects	63 (mg/kg
	(Workers)		bw/day)
	DNEL	Dermal, Chronic, Systemic effects	37 (mg/kg
	(Consumers)		bw/day)
xylene	DNEL	Inhalation, Chronic, Systemic effects	77
CAS No: 1330-20-7	(Workers)		(mg/m³)
EC No: 215-535-7			
2,6-di-tert-butyl-p-cresol	DNEL	Inhalation, Chronic, Systemic effects	3,5
CAS No: 128-37-0	(Workers)		(mg/m³)
EC No: 204-881-4			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
othyl acetate	sediment (freshwater)	1,15 (mg/L)
ethyl acetate CAS No: 141-78-6	sediment (marine water)	0,115 (mg/L)
EC No: 205-500-4	Soil	0,148 (mg/kg
LC No. 203-300-4		soil dw)
	STP	650 (mg/L)
	oral (Hazard for predators)	0,2 (g/kg
		food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %	
Uses:	ADHESIVO MULTIUSOS	
Breathing protect	tion:	
PPE:	Filter mask for protection against gases and particles.	
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.	(00)
CEN standards:	EN 136, EN 140, EN 405	

(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Date of compilation: 30/10/2019 Version 1

Page 6 of 12 Print date: 20/11/2024 Version 26 (replaces version 25) Revision date: 06/03/2024

Should not be stored in places exposed to high temperatures and damp environments before use. Special Maintenance:

attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.

Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach Observations: the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols:

P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.

Filter Type needed:

Hand protection:

PPF. Protective gloves.

Characteristics: «CE» marking, category II.

CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420

Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible.

Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or

adhesives.

Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Observations:

Always use with clean, dry hands.

Breakthrough time Material thickness Material: PVC (polyvinyl chloride) > 480 0,35 (min.): (mm):

Eye protection:

CFN standards:

Observations:

PPE: Face shield.

Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid.

CEN standards: EN 165, EN 166, EN 167, EN 168

Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance:

be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move

Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm Observations:

vertically once attached to the frame. Skin protection:

Anti-static protective clothing. PPE:

«CE» marking, category II. Protective clothing should not be too tight or loose in Characteristics:

order not to obstruct the user's movements. EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5

In order to quarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance:

the manufacturer.

The protective clothing should offer a level of comfort in line with the level of protection provided in

terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level

of activity and the expected time of use

PPF. Anti-static safety footwear. Characteristics: «CE» marking, category II.

EN ISO 13287, EN ISO 20344, EN ISO 20346 CEN standards:

Maintenance: The footwear should be checked regularly

The level of comfort during use and acceptability are factors that are assessed very differently depending

Observations: on the user. Therefore, it is advisable to try on different footwear models and, if possible, different

widths

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid Colour: Beige

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: 65 °C (Estimations in base on the Regulation (CE) Nº1272 / 2008

indications.)

Flammability: Not available

Lower explosion limit: 1.1 (Determination of the explosion limits and the limiting oxygen concentration (LOC) for flammable gases

and vapours. (UNE-EN 1839:2017)) Upper explosion limit: Not available

Flash point: -4 °C



(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Date of compilation: 30/10/2019 Version 1

Page 7 of 12 Version 26 (replaces version 25) Print date: 20/11/2024 Revision date: 06/03/2024

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: Not applicable (Substance/mixture is non-soluble (in water)). Kinematic viscosity: Not applicable (Not relevant for this type of product)

Solubility: Not available Hydrosolubility: Not available Liposolubility: Not available

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not available

Absolute density: 1,25-1,27 kg/m3 (calculation/estimation)

Relative density: Not available

Relative vapour density: 3.5 m3/kg (calculation/estimation)

Particle characteristics: Not available

9.2 Other information

Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

Other safety characteristics

Viscosity: Not applicable Dropping point: Not available Blink: Not available % Solids: Not available

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.


IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name		Acute toxicity				
Name	Туре	Test	Kind	Value		
hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6)) (Mixture of isomers)	Oral	DL50	Rat	>16750 mg/Kg bw [1]		
Thexame (203 777 0)) (Flixture of Isomers)		[1] TOTAL				



(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Version 1 Date of compilation: 30/10/2019

Version 26 (replaces version 25) Revision date: 06/03/2024 Print date: 20/11/2024

			DL50	Rabbit	>3350 mg/Kg bw (4 h) [1]
		Dermal			3, 3 () []
			[1] TOTA	L	
			CL50	Rat	259354 mg/m3 (4 h) [1]
CAC No.	EC No.	Inhalation			
CAS No:	EC No:		[1] Total		

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 110.000 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity				
Name	Туре	Test	Kind	Value	
hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6)) (Mixture of isomers)	Fish	LL50	Oncorhynchus mykiss	18.3 mg/l (96 h) [1]	
		[1] Total			
	Aquatic	EL50	Daphnia magna	31.9 mg/l (48 h) [1]	
	invertebrates	[1] Total			



Page 8 of 12

(in accordance with Regulation (EU) 2020/878)





Nail Free Fix

Date of compilation: 30/10/2019 Version 1

Page 9 of 12 Version 26 (replaces version 25) Print date: 20/11/2024 Revision date: 06/03/2024

			Aquatic plants	ErL50	Pseudokirchneriell a subcapitata	13.6 mg/l (72 h) [1]
CA	AS No:	EC No:	1	[1] Total		

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Namo		Bioaccumulation				
Na	Name		BCF	NOECs	Level	
ethyl acetate		0,73		_	Very low	
CAS No: 141-78-6	EC No: 205-500-4	0,73	-	-	very low	
hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6)) (Mixture of isomers)		3,6	501	-	Moderate	
CAS No:	EC No:	5,5	301		riodoraco	

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG. Transport documentation: Bill of lading Air: Transport by plane: ICAO/IATA. Transport document: Airway bill.

(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Date of compilation: 30/10/2019 **Version 1**

Page 10 of 12 Version 26 (replaces version 25) Print date: 20/11/2024 Revision date: 06/03/2024



14.1 UN number or ID number.

UN No: UN1133

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1133, ADHESIVES, 3, PG II, (D/E) IMDG: UN 1133, ADHESIVES, 3, PG II (-4°C) UN 1133, ADHESIVES, 3, PG II ICAO/IATA:

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D

14.6 Special precautions for user.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 1 L



14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC) VOC content (p/p): 39 %

VOC content: 551,338 g/l

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
Liquid substances or mixtures fulfilling	1. Shall not be used in:
the criteria for any of the following hazard	- ornamental articles intended to produce light or colour effects by means of
classes or categories set out in Annex I to	different phases, for example in ornamental lamps and ashtrays,
Regulation (EC) No 1272/2008:	- tricks and jokes,
(a) hazard classes 2.1 to 2.4, 2.6 and 2.7,	- games for one or more participants, or any article intended to be used as
2.8 types A and B, 2.9, 2.10, 2.12, 2.13	such, even with ornamental aspects,
categories 1 and 2, 2.14 categories 1 and 2,	2. Articles not complying with paragraph 1 shall not be placed on the market.
2.15 types A to F;	3. Shall not be placed on the market if they contain a colouring agent, unless
(b) hazard classes 3.1 to 3.6, 3.7 adverse	required for fiscal reasons, or perfume, or both, if they:

(in accordance with Regulation (EU) 2020/878)

Nail Free Fix

Date of compilation: 30/10/2019 Version 1

Page 11 of 12 Version 26 (replaces version 25) Print date: 20/11/2024 Revision date: 06/03/2024



effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;

- (c) hazard class 4.1;
- (d) hazard class 5.1.

- can be used as fuel in decorative oil lamps for supply to the general public, and.
- present an aspiration hazard and are labelled with H304.
- 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
- 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
- (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';
- (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';
- (c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly Hammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Highly flammable liquid and vanour

Classification codes:

חססב

Acute Tox. 4: Acute toxicity (Dermal), Category 4 Acute Tox. 4: Acute toxicity (Inhalation), Category 4

Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1 Aquatic Chronic 2: Chronic effect to the aquatic environment, Category 2 Aquatic Chronic 3: Chronic effect to the aquatic environment, Category 3

Asp. Tox. 1: Aspiration toxicity, Category 1 Eye Irrit. 2: Eye irritation, Category 2 Flam. Liq. 2: Flammable liquid, Category 2 Flam. Liq. 3: Flammable liquid, Category 3

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Skin Irrit. 2: Skin irritant, Category 2

Changes regarding to the previous version:

- National legislative changes (SECTION 15.1).

(in accordance with Regulation (EU) 2020/878)

Nail Free Fix



Date of compilation: 30/10/2019 Version 1

Page 12 of 12 Print date: 20/11/2024 **Version 26 (replaces version 25)** Revision date: 06/03/2024

- Elimination of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method **Environmental hazards** Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

Agreement concerning the International Carriage of Dangerous Goods by Road. ADR:

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

EC50: Half maximal effective concentration. PPE: Personal protection equipment. TATA: International Air Transport Association. ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

No observed effect concentration. NOEC:

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/ Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.